

___	AIR VENT BULB	Cleanout	
___	REFILL	Differential (80/90) Gearbox (engine oil)	
___	FRONT SUSPENSION	Inspect Tighten dampers Lube kingpins Top Off front dampers Inspect flex & steel brake lines →	FRONT SUSPENTION INSPECTION ___ kingpins ___ distance tubes ___ A Arms ___ bushings ___ tie rod ends ___ inner tie rod ends
___	FRONT BEARINGS	Remove pads Inspect hub end float Grease outer bearings Adjust hub end float	
___	FRONT BRAKES	Exercise front calipers Bleed rear and front brakes Exercise – Lube – Adjust handbrake	
___	RACK& PINION	Inspect bellows Lube rack Adjust shim pack Inspect U joint	
___	BONNET CABLE	Lube & Exercise Lube funnel Lube bonnet support	
___	VENT CONTROLS	Lube & Exercise the AIR control TEMP control	
___	UNDERBONNET	Top off master cylinders, carbs washer solvent Inspect and adjust fan belts Inspect engine mounts-brackets Replace oil filter Refill engine	Oil Brand _____ Oil Weight _____
___	COOLING SYS	Loosen-Retighten 15 hose clamps Pressure Check to 15psi Test antifreeze Record Antifreeze guidelines → Lube electric cooling fans	Antifreeze Temperature GOOD to _____°F
___	FUSEBOX	Remove & Sandblast Disconnect or Fuse OD or TCSA wiring (WHITE, WHITE/BROWN, YELLOW)	
___	CARBURETTER	Inspect and replace if needed: air filer	air filer brand _____

	fuel filter PCV lines Tighten auto choke	fuel filter brand _____
___ WIPERS	Inspect / Replace wiper blades Inspect / Adjust wiper park position Clear/ Adjust washers	Wiper Blade Brand _____ Right blade size _____ Left blade size _____
___ INTERIOR	Lube seat rails – door strikers Oil door latches Tighten door latches – Inspect visors and rear view mirror Inspect gear knob	
___ PEDALS	Inspect & Adjust free play for clutch brake throttle	
___ BOOT	Inspect – Lube jack – support Tighten boot latch Inspect tonneau – ½ tonneau – tonneau bars Inspect / replace ELC lines	
___ SOFT TOP	Inspect snaps – Lift-the-Dot studs – latches – windows Tighten top bow screws	
___ TIRES	Inflate to 30 psi front 32 psi rear	LF _____ RF _____ LR _____ RR _____
___ BATTERY	Wash in soda Clean-Replace Clamps Clean cables Tie Down Record gravity →	RECORD GRAVITY: +1 _____ 2 _____ 3 _____ 4 _____ 5 _____ 6 _____ -
___ REAR SHOCKS	Top Off	
___ SEAT BELTS	Inspect operation (withdrawal – recoil – latch – fixings)	
___ EXTERIOR	Inspect / Tighten antenna door handles overriders grille mirrors	

___ **FIRE
EXTINGUISHER**

Inspect

Expiration date _____

___ **LIGHTS**

Inspect operation of all lights listed below

LAMPS & LIGHTS

LEFT FRONT EXTERIOR SIDE PARK TURN HORN HIGH BEAM LOW BEAM	INTERIOR IGNITION LITE DASH RHEO BRIGHT FLASH HAZARDS INTERIOR LEFT TURN / CANCEL / RIGHT TURN BOOT LIGHT	RIGHT FRONT EXTERIOR HORN TURN PARK SIDE HIGH BEAM LOW BEAM
LEFT REAR EXTERIOR SIDE PARK TURN REVERSE BRAKE LICENSE PLATE		RIGHT REAR EXTERIOR REVERSE TURN PARK SIDE LICENSE PLATE BRAKE

See Test Drive Checklist